






Lodge 220

TECHNICAL DATA SHEET

PRODUCT SPECIFICATIONS		EN
Multilayer Oak wood flooring	EN 13489 (Free Class)	DOP PQ2022-6
Dimensions	Plank	600-2200 x 220 x 15/ 4 mm
	Box	6 planks / 2,904 m ² / 24.5 kg
	Nested lengths	Max 2 per box (min 600 mm)
	Pallet	40 boxes / 116.16 m ² / 1005 kg
Density	EN ISO 23996	+/- 650 kg/m ³
Installation	ISO 24334	Drop Lock (floating or glued)
Top Layer		4 mm European oak (Quercus Robur)
Grading		Rustical (B+)
Surface		slightly brushed
Bevel		4 -sided bevel
Finishing		Oxidative oil
Gloss Level	60°	5-10 %
Warranty conditions	Residential Use Commercial Use	20 years upon request
Application	EN 13489	Class 23 – Heavy residential use



PRODUCT PROPERTIES			
PROPERTY	TEST METHOD	MIN. REQ.	RESULT
Indoor air certifications			A
Fire resistance	 EN 13501-1		Cfl-s1
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorophenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0.13 m ² K/W OK (max +28°C) + glued
Transit sound reduction	 EN ISO 10140		ΔLw 19 dB Underlay 'Moist & Sound' (floating installation)
Biological durability			Class 1

Cleaning and maintenance instructions see : www.lamett.eu

